

Avaya Business Communications Manager 50

Technical Specifications

Physical Specifications		Regulatory compliance	
Depth	12.75 in.	Canada CS-03 and US	
Width	8.625 in.	Federal Communications Commission (FCC) Part 68 and has been registered under files Industry Canada 332D-5980A and FCC US: AB6KF15B20705 (key system), US: AB6MF15B20706 (hybrid system) and US: AB6PF15B23740 (PBX system). BCM50 Model No. NT7B10xxxx is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC. European Safety requirements EN 60950 and EMC requirements EN 55022 (Class A) and EN 55024.	
Height	2.625 in.	Electromagnetic emissions	
Weight	BCM50 4 lb. 1.9 oz.; BCM50a/e 4 lb. 8.6 oz.	BCM50 equipment meets all FCC Part 15, Class A radiated and conducted emissions requirements. BCM50 does not exceed the Class A limits for radiated and conducted emissions from digital apparatus as set out in the Radio Interference Regulations of Industry Canada.	
MBM	2 w/Expansion Unit	Electromagnetic compliance	
CPU	PowerQuickII 8270	The Avaya BCM50, BCM50 with ADSL Router (BCM50a), BCM50 with Ethernet Router (BCM50e) and BCM50 Expansion Unit fully comply with the following standards and specifications:.	
Memory	256 Mbytes of SDRAM	Canada	ICES-003 Class A using: — CISPR 22 (1997) Class A — ANSI C63.4 (2001) method
Hard Drive	40G Serial ATA HD	United States	FCC Part 15 Subpart B Class A using: — CISPR 22 (1997) Class A — ANSI C63.4 (2001) method
System status LEDs	Status and Power	European Union	EN55024 (1998 w/A1:01 & A2:03)/ CISPR 24 (1997) excluding Annex A EN55022 (1998) Class A EN61000-3-2 (2001) EN61000-3-3 (1995 w/A1:98)
Mounting options	Desk top, wall mount or rack mount	Australia/New Zealand	AS/NZS CISPR 22 (2002) Class A using: — EN55022 (1998) Class A
Power supply specifications	AC input: 100-240V -2 A, 50-60 Hz; DC output: 19 6.32 A	Japan	VCCI (April 2000) Class A using: — CISPR 22 (1997) — ANSI C63.4 (2001) method
Operating temperature	-5°C to 50°C	Mechanical requirements	
Operating humidity	90-95% RH at 40°C	Packaged	
Storage temperature	-55°C to 70°C	<ul style="list-style-type: none"> • Transportation vibration as per Telcordia GR-63 (Section 5.4.3, Figure 4-3, Curve 2) • Transportation bounce as per IEC 68-2-55 (Method A) • Drop and vibration as per ISTA Procedure 1A 	
Storage humidity	90-95% RH at 40°C	Unpackaged (Operational)	
		<ul style="list-style-type: none"> • Office vibration as per Telcordia GR-63 (Section 5.4.2, Electronic Subassemblies) • Mechanical shock as per IEC 68-2-27 (Test Ea) • Drop as per IEC 68-2-32 (Test Ed) 	

The following specific tests were performed to verify the above certifications		
Radiated Emissions	EN55022 (1998)	Class A
Mains Conducted Emissions	EN55022 (1998) CISPR 22 (1997)	Class A
Harmonic Emissions	EN61000-3-2 (2001)	
Voltage Fluctuations and Flicker Emissions	EN61000-3-3 (1995 w/A1:98)	
Electrostatic Discharge	EN61000-4-2 (1995) EN55024 (1998 w/A1:01 & A2:03 CISPR 24 (1997)	+/- 4kV contact +/- 8kV air
Radiated E-Field Immunity	EN61000-4-3 (1997) EN55024 (1998 w/A1:01 & A2:03 CISPR 24 (1997)	3 V/m
Electrical Fast Transient Burst	EN61000-4-4 (1995) EN55024 (1998 w/A1:01 & A2:03 CISPR 24 (1997)	1 kV (AC) 0.5 kV (I/O)
Surge	EN61000-4-5 (1995) EN55024 (1998 w/A1:01 & A2:03)	2 kV (AC) 1 kV (AC)
Conducted Immunity	EN61000-4-6 (1996) EN55024 (1998 w/A1:01 & A2:03 CISPR 24 (1997)	3 Vrms
Voltage Dips and Interrupts	EN61000-4-11 (1994) EN55024 (1998 w/A1:01 & A2:03 CISPR 24 (1997)	
Network protection		
Safety and surge/transient		

MBM
BCM50 main unit
<ul style="list-style-type: none"> • One Amphenol (male) connector (25 pair) • 4 loop start CLASS/CMS lines (keycode enabled) • 4 analog station ports [disconnect supervision - 850 Ms Momentary Disconnect, Message Waiting Indication - NA 120V 600 ms on and 1000 off, Calling Line • 12 digital phone ports (keycode enabled)
Embedded modem
<ul style="list-style-type: none"> • BCM50 — standard soft modem support on analog lines

BCM50
<ul style="list-style-type: none"> • Craftsperson interface — 10/100 auto sensing/auto polarity; RJ-45 connector, DHCP support
<ul style="list-style-type: none"> • Customer access — 10/100 auto sensing/auto polarity; RJ-45 connector, DHCP support
<ul style="list-style-type: none"> • Expansion port or 10/100 auto sensing/auto polarity switch port; RJ-45 connector, DHCP support
<ul style="list-style-type: none"> • Expansion port or 10/100 auto sensing/auto polarity switch port; RJ-45 connector, DHCP support

BCM50a and BCM50e
<ul style="list-style-type: none"> • 4 10/100 auto sensing/auto polarity switch port; DHCP support

Telephony components

MSC interfaces
<ul style="list-style-type: none"> • BCM50 Main unit — Recessed reset button; USB interface, Music on Hold Interface [3.5mm (1/8 inch) standard miniature stereo (3 conductor)]; Auxiliary Ringer, Page Relay, Page Output and Music on Hold on Amphenol (male) connector (25 pair)

WAN interface

BCM50a
<ul style="list-style-type: none"> • ADSL interface, RJ-45 connector

BCM50e
<ul style="list-style-type: none"> • 10/100 auto sensing/auto polarity; RJ-45 connector

Expansion cabinets

BCM50 Expansion Unit	
<ul style="list-style-type: none"> • One Media Bay Module slot • Supports all BCM Media Bay Modules except FEM and DDIM • Maximum two Expansion Units per BCM50 • Utilizes standard 10/100 LAN cable for the interface to the BCM50 main unit • Supports 3 10/100 auto sensing/auto polarity switch port; DHCP support 	
Depth	12.75 in.
Width	8.625 in.
Height	2.625 in.
Weight	2 lb. 5.2 oz

The specifications above also apply to the BCM50b, BCM50ba and BCM50be versions (for EMEA and APAC only) with integrated BRI trunks.

In the United States:

Avaya
35 Davis Drive
Research Triangle Park, NC
27709 USA

In Canada:

Avaya
195 The West Mall
Toronto, Ontario M9C 5K1
Canada

In Caribbean and Latin America:

Avaya
1500 Concorde Terrace
Sunrise, FL 33323 USA

In Europe:

Avaya
Maidenhead Office Park,
Westacott Way
Maidenhead Berkshire SL6 3QH
UK

In Asia:

Avaya
United Square
101 Thomson Road
Singapore 307591

About Avaya

Avaya is a global leader in enterprise communications systems. The company provides unified communications, contact centers, and related services directly and through its channel partners to leading businesses and organizations around the world. Enterprises of all sizes depend on Avaya for state-of-the-art communications that improve efficiency, collaboration, customer service and competitiveness. For more information please visit www.avaya.com.



INTELLIGENT COMMUNICATIONS

© 2010 Avaya Inc. All Rights Reserved.

Avaya and the Avaya Logo are trademarks of Avaya Inc. and are registered in the United States and other countries.

All trademarks identified by ®, TM or SM are registered marks, trademarks, and service marks, respectively, of Avaya Inc.

All other trademarks are the property of their respective owners. Avaya may also have trademark rights in other terms used herein.

References to Avaya include the Nortel Enterprise business, which was acquired as of December 18, 2009.

03/10 • SME5186

avaya.com